

ADJUSTABLE SHELVING SYSTEM

by

Bryan Thomas Johnson

BACKGROUND

This application is a non- provisional application filed under U.S.C. §111(a) claiming priority of the provisional application serial no. 60/430516 filed 12/3/2002.

Numerous heavy duty shelving systems have been provided in prior art that are adapted to include rigid frames having rigid shelving. While these units may be suitable for the particular purpose to which they address, they would not be as suitable for the purposes of the present invention as hereinafter described.

SUMMARY

The present invention is directed to an adjustable shelving system that satisfies these needs for an economical, heavy-duty, adjustable shelf system for industrial, commercial, and home use that provides easy adjustment of shelving, easy storage of unused shelves, and a mobile optional. A shelving system having features of the present invention comprises a rigid shelf frame support having side rail tubes and removable support arms that may be releasably attached in pairs along both a front and back side of the side rail tubes. A pair of support arms have mounted thereon a shelf. Each support arm has a J-shaped bracket at one end thereof with a pin mounted on the bracket. One of each pair of support arms has a J-shaped bracket with a unique shaped pin. Both the pin and the shaped pin are received by one of a series of regularly placed orifices in each generally square-shaped side rail tube. The J-shaped bracket fits about three sides of the generally square-shaped side rail tube thereby firmly supporting the support arm and attached shelf once in position.

The shelf can be a flat shelf, lipped shelf, a basket or the like. In use, one of the pair of support arms having a shaped pin is inserted manually whereby the shaped pin locks into place in the side rail tube orifice and pivots therein for ease of attachment of the second support arm of the pair having a pin mounted on the bracket. This system enables the user to attach one of the pair of

1 support arms, with the shaped pin, to the side rail and then attach the second support arm without
2 having the first support arm fall out of place.

3 The side rail tubes, in actual use conditions of high carbon, heat treated steel, have spaced
4 apart pin receiving orifices placed at regular intervals in two sides of each side rail tube enabling the
5 shelving system to be placed on both a front and back side of the side rail tubes. In actual use
6 conditions, the side rail tubes are generally square shaped although other shapes could be utilized.
7 Other resilient materials could also be used.

8 The various features of novelty which characterize the invention are pointed out with
9 particularity in the claims annexed to and forming a part of this disclosure. For a better understanding
10 of the invention, its operating advantages and specific objects attained by its uses, reference is made
11 to the accompanying drawings and descriptive matter in which a preferred embodiment of the
12 invention is illustrated.

15 BRIEF DESCRIPTION OF THE DRAWINGS

16 Understanding of the invention will be enhanced by referring to the accompanying drawings,
17 in which like numbers refer to like parts in the several views and in which:

18 Fig. 1 is a perspective view of the optional mobile device of this invention;

19 Fig. 2 is a perspective view of the wall mounted version of the device of this invention;

20 Fig. 3 is a close-up view of the support arm showing the J-shaped bracket and shaped pin;

21 Fig. 4 is a close-up view of the support arm showing the J-shaped bracket and pin;

22 Fig. 5 is a fragmented view of the pair of support arms showing the J-shaped bracket with a
23 shaped pin and a J-shaped bracket with a pin; and

24 Fig. 6 is an in use cross-sectional view as indicated by arrows in Fig. 1 with the shaped pin
25 shown received by the side rail orifice and the other pin shown in phantom about to be received by
26 the opposite side rail orifice.

DETAILED DESCRIPTION OF THE CURRENTLY PREFERRED EMBODIMENTS

Understanding of the invention will be further enhanced by referring to the following illustrative but non-limiting example.

An adjustable rigid shelving storage system for use in industrial, commercial and home settings where available floor space is limited, the storage system having supports arms with a unique bracket for releasable attachment to side rail uprights whereby the support arms may be reversed for flat storage when not used. The adjustable shelving storage system is provided in wall-mounted, floor mounted and mobile versions. Additionally, a plurality of these systems may be nested together for storage thereof.

Turning now to the drawings, in which like reference characters refer to corresponding elements throughout the several views, **Fig. 1** illustrates the adjustable shelving system **10**, from the top down, with a pair of support arms **26, 26'**, first without a shelf attached for ease of understanding, in a position of use extending from the side rail **22**. Next is shown a pair of support arms **26, 26'** with shelf **36** attached in a position of shelf storage, parallel to the side rail **22**. At the bottom is illustrated pair of support arms **26** with shelf **36** attached in a position of use extending generally horizontally from the side rail **22**. The side rails **22**, in actual use conditions of high carbon, heat-treated generally square steel tubing, have spaced apart pin receiving orifices placed at regular intervals in two sides of each side rail **22** enabling the shelving system **10** to be placed on both a front and back side of the side rail **22**. In actual use conditions, the side rail **22** are generally square shaped although other shapes could be utilized. Other resilient materials could also be used.

J-shaped bracket **30, 30'** shown in detail in **Figs. 3 & 4**, has three inner surfaces that wrap around the generally square-shaped side rail **22**. J-shaped bracket **30'**, shown in detail at **Fig. 3** has three inner surfaces that wrap around the generally square-shaped side rail **22**. **Fig. 3** illustrates J-shaped bracket **30'** having a first surface **82** on which is mounted shaped pin **32**, second surface **84** extending at a generally right angle from the first surface **82** and a third surface **86** extending at a generally right angle from second surface **84**.

Fig. 4 illustrates J-shaped bracket **30** having a first surface **82** on which is mounted pin **30** and second surface **84** extending at a generally right angle from the first surface **82** and a third surface **86** extending at a generally right angle from second surface **84**.

1 J-shaped bracket 30,30', shown in detail at Fig. 3 & 4, has three inner surfaces that wrap around
2 and lock into place about the generally square-shaped side rail 22. Fig. 3 illustrates J-shaped
3 bracket 30' having a first surface 82 on which is mounted shaped pin 32, second surface 84
4 extending at a generally right angle from the first surface 82 and a third surface 86 extending at a
5 generally right angle from second surface 84.

6 Attachment of J-shaped bracket 30, 30' at a first end 21 of each support arm 26,26',
7 permits the support arm 26, 26' to be supported on three sides when in its position of use thereby
8 providing a strong base of support for the support arm 26, 26'. J-shaped bracket 30, at a first end
9 of each support arm 26,26', may be released from attachment to the side rail and reversed such that
10 the formerly left side is attached to the right side rail, and vice versa, such that the attached shelf or
11 the like hangs downwardly in a generally vertical, out-of-the-way position, as indicated by support
12 arm 26 in Fig. 1. The J-shaped bracket 30 also permits the support arm 26, 26' to be adjusted
13 upwardly and downwardly along the side rail 22. The J-shaped bracket 30 also permits the support
14 arm 26 to be reversed, where the formerly left side bracket is attached to the right side rail 22 and
15 vice versa, permitting out of the way storage of both the support arm 26 and the shelf 36 mounted
16 thereon. Cross pieces 44 are shown in Fig. 1 mounted on a base 46 interconnecting and stabilizing
17 the side rails 22 in a optional portable version having wheels 40. It is recognized that other shelves
18 36, such as flat, lipped, or table surface, could be used with equal success. It is also recognized that
19 in each pair of support arms 26, 26' one of the pair has a shaped pin 32 attached to one of the pairs
20 and a pin 34 attached to the other of each pair.

21 Fig.2 illustrates a wall mounted system 10' with wall-mounted fasteners 50 attaching the pair
22 of side rails 22 to a wall or other upright surface. Again, the shelf attached support arms 26, 26' are
23 shown in a storage position and a position of use 26, 26'.

24 Fig. 3 shows a support arm 26' having shelf-receiving apertures 38 formed therein whereby
25 any type of shelf could be attached. J-shaped bracket 30' is shown mounted on a first end 21 of
26 support arm 26'. The J-shape of bracket 30' provides support to the attached support arm 26'
27 because the J-shaped bracket 30 abuts the side rail 22 on three sides. Once the J-shaped bracket 30
28 is in place, it remains locked in position until such time as the user lifts up one end of the support arm
29 26. Fig. 3 also illustrates the shaped pin 32 which has a cap 33 that is manually pushed through a

1 pin orifice 24 allowing the attached support arm 26, 26' to be pivoted about a neck 35 of shaped pin
2 32 allowing easy positioning of both of the pair of any support arms 26, 26'. Thus a first of the pair
3 of support arms 26' is mounted on a side rail 22 and the second of the pair of support arms 26 may
4 be positioned without the first support arm 26' falling out of position. This shaped pin 32 releasably
5 locks into place in a pin orifice 24 in a side rail 22. This permits the basket shelf 36, or other shelf
6 or table top, to be positioned on one side, locked into place supporting the weight of the basket and
7 support arm 26' and then the second support arm 26 is easily positioned by placing the pin 30 of the
8 second support arm 26 into the selected pin orifice 24 of the appropriate side rail 22.

9 Fig.4 illustrates the support arm 26 with a J-shaped bracket 30 mounted on a first end 21 of
10 support arm 26 with pin 34 shown with a tapered end 37 for ease of receipt by pin orifice 24. In use,
11 the support arm 26' with shaped pin 32 is locked into position such that it pivots, as described above
12 and illustrated at Fig. 3, and then the second of the pair of support arms 26 having pin 34 attached
13 to J-shaped bracket 30 is received by the selected pin orifice 24 of side rail 22 with the pair of
14 support arms 26, 26' supported by three-sided J-shaped bracket 30, 30' locked into place about the
15 side rail 22 firmly supporting the weight of the basket, shelf, table top and items placed thereon.

16 Fig. 5 illustrates a close-up view of the J-shaped bracket 30 showing how the bracket 30
17 receives the square-shaped side rail 22, as shown in Fig.1, and fits about three sides of the rail 22
18 gaining firm support from the side rails 22. Shaped pin 32 is shown with cap 33 and neck 35
19 shown. Pin 34 is shown with a taper 37 to aid in receipt by pin orifice 24 as shown in Fig. 1.

20 Fig. 6 illustrates how a first support arm 26' with shaped pin 32 is received by pin orifice 24
21 with the pin cap 33 fitting into the pin orifice 24 such that the shaped pin 32, on the bracket 30'
22 mounted on a support arm 26', pivots about the shaped pin neck 35 allowing the attached shelf 36
23 mounted to the second of the pair of support arms 26 with a bracket 30 and pin 34 mounted thereon,
24 such that the first of the pair of support arms 26' is attached and locked into place while the second
25 support arm 26 may be positioned on the adjacent side rail 22 at the selected pin orifice 24, shown
26 in phantom.

27 Adjustable shelving storage system 10 may be mounted on a base 46 with or without wheels
28 40 as illustrated in Fig.1. Adjustable shelving storage system 10 may also be wall mounted, as shown
29 in Fig. 2. Additionally, multiple adjustable shelving storage system units 10 may be nested, with the

1 shelf baskets or other shelf or table surfaces, in the generally flat position, such that multiple
2 adjustable shelving storage systems 10 may be place adjacent each other for storage whereby a small
3 amount of floor space is needed to store several adjustable shelving storage systems 10. This is
4 accomplished by removing shelf mounted support arm 26, 26' may be removed and reversed such
5 that what was formerly on the left side rail 21 now is positioned on the right side rail and vice versa
6 permitting flat, out-of- the way storage.

7 Although the present invention has been described in considerable detail with reference to
8 certain preferred versions thereof, other versions are possible. For example, a combination of these
9 systems may be used in a setting where shelf storage is needed, such as a garage, display area, and
10 industrial areas.

11 Changes and modifications in the specifically described embodiments can be carried out
12 without departing from the scope of the invention.